

# installation guide

## Trucore Architectural Timber Doors

### Handling & Storage

All Pelican Systems timber doors are despatched from the factory pre-wrapped in protective packaging with timber support blocks to protect the bottom edge of the doors from damage. To ensure your doors remain in the same state of quality as they left the factory we recommend the following on site handling tips:

- Doors must never be stored in an upright position with the top edge against a wall. This is the most common cause of doors bowing on site.
- Doors should be stored on a flat, level surface.
- Ideally doors should be stored on a protective board of at least 16mm in thickness with levelling bearers.
- Doors should never be stored in or near direct sunlight. This can result in veneer discolouration within a few hours.
- Do not sit on top of or store anything on top of or against timber doors being stored on site.
- Ensure the storage area is dry and well-ventilated.
- Exercise caution when moving and fitting doors to ensure door edges and faces are not damaged.
- Doors, as a finishing product should be installed as late as possible in the building program to prevent damage from other trades.



DIN EN 9001:2000  
CERTIFICATE NO. 01 100 8280061  
ISO CERTIFICATION FOR DURBAN ONLY

Tel: +27(0)31 563 7307  
Website: [www.pelican.co.za](http://www.pelican.co.za)  
Email: [info@pelican.co.za](mailto:info@pelican.co.za)

