



product  
*News*

April 2015

# jumbo insulation

JUMBO Insulation is categorised as a flexible polyester blanket and is 100% recyclable as well as being easy and safe to work with. JUMBO Insulation is non-toxic, there are no chemical additives and it is completely odourless.

There will be no itching, no loose fibres and no need to wear protective clothing or worry about your employee's health during handling and installation.

JUMBO Insulation has been fire tested in accordance with SANS 10177-10 (428) achieving the classification B/B1/2.



Mark 9486/15037

JUMBO Insulation is FULLY COMPLIANT and has the SABS test and mark.

Determine the "R"- Value you need to achieve for the climatic area and type of roof construction and you can select the thickness you require.



Thickness	"R"-Value
50mm	1.15
100mm	2.20
135mm	2.70

The higher the R- VALUE the greater the insulation effect.

### PRODUCT SPECIFICATIONS

Thickness	Metres per Roll	Roll width	Area Covered in m <sup>2</sup> per Roll	Density per Roll kgs/m <sup>3</sup>	*Weight per Roll in kgs	"R" Value	Packaging Colour
50mm	10	1.200	12.0	10.1	6	1.15	Green
100mm	6	1.200	7.2	10.1	7.2	2.20	Yellow
135mm	5	1.200	6.0	10.1	8.1	2.70	Purple

\* Note: 10% variance allowable either up or down



Management System  
ISO 9001:2008



www.tuv.com  
ID 9105031796

Head Office / Durban (031) 563 7307 | Pietermaritzburg (033) 345 3701  
 For export and all other regions contact our head office or one of our distributors.  
[info@pelican.co.za](mailto:info@pelican.co.za) | [www.pelican.co.za](http://www.pelican.co.za)  
 Find us online at any of these social media sites

