

## Pelican JUMBO FireWALL 63/120

**Fire Rating: 2 Hours**

Supply and fit Pelican Systems JUMBO FireWALL 63/120 with overall thickness of 124mm, with 63 x 35mm JUMBO studs at 600mm centres friction fitted into head track and floor track and clad on both sides with a double layer of 15mm thick Fire Resistant JUMBO Plasterboard fixed at 200mm centres using 25mm JUMBO Screws on the base layer and 42mm JUMBO Screws on the face layer, all plasterboard joints must overlap. All exterior joints to be covered with JUMBO Tape and finished with two layers of JUMBO Jointing Plaster applied and lightly sanded down, leaving wall surface prepared for painting, all in accordance with the supplier's recommendations.

## Pelican JUMBO FireWALL 63/120/S56

**Fire Rating: 2 Hours**

**Sound DB Rating: 56dB**





Supply and fit Pelican Systems JUMBO FireWALL 63/120/S56 with overall thickness of 124mm, with 63 x 35mm JUMBO studs at 600mm centres friction fitted into head track and floor track and clad on both sides with a double layer of 15mm thick Fire Resistant JUMBO Plasterboard fixed at 200mm centres using 25mm JUMBO Screws on the base layer and 42mm JUMBO Screws on the face layer, all plasterboard joints must overlap. All exterior joints to be covered with JUMBO Tape and finished with two layers of JUMBO Jointing Plaster applied and lightly sanded down, leaving wall surface prepared for painting, all in accordance with the supplier's recommendations. A 14kg/m<sup>3</sup> density insulation to be installed in the cavity.



KZN Head Office: (031) 563 7307  
[www.pelican.co.za](http://www.pelican.co.za)  
[info@pelican.co.za](mailto:info@pelican.co.za)

Find this specification on



 ceiling systems  partitioning systems  opening systems  flooring systems