

## Pyropanel Fire Doors

Standard Fire Rated Hinged Doorsets

(1 and 2 hour rating or SABS class A,B & D)

(Specifications for all other pyropanel fire rated doorsets are available on request.)

1 Hour or 2 Hour Fire Rated Doorsets

Supply and install Pyropanel fire rated doorsets in strict accordance with the manufacturer's instructions and in compliance with SABS 1253 : 2003 for a 60 or 120 minute fire rating with 3.6mm treated commercial ply or masonite suitable for painting on both sides. Including intumescent strip to top of door, hardwood edges, specified ironmongery and hinged one side to suitable 1.6mm gauge red oxide primed mild steel / galvanized steel frame.

1. Single Leaf door 810 x 2030 x 48mm including frame suitable for 115mm / 230mm brick wall.
2. Unequal Leaf Double door 1200 x 2030 x 48mm including frame suitable for 115mm / 230mm brick wall.
3. Equal Leaf Double door 1620 x 2030 x 48mm including frame suitable for 115mm / 230mm brick wall.
4. Single Leaf door 810 x 2030 x 48mm including 100 x 300mm vision panel with Pyroceramic fire resistant glass and frame suitable for 115mm / 230mm brick wall.
5. Unequal Leaf Double door 1200 x 2030 x 48mm including 100 x 300mm vision panel with Pyroceramic fire resistant glass to each leaf and frame suitable for 115mm / 230mm brick wall.
6. Equal Leaf Double door 1620 x 2030 x 48mm including 100 x 300mm vision panel with Pyroceramic fire resistant glass to each leaf and frame suitable for 115mm / 230mm brick wall.
7. Frames suitable for fire rated drywalls are available on request.



KZN Head Office: (031) 563 7307

[www.pelican.co.za](http://www.pelican.co.za)

[info@pelican.co.za](mailto:info@pelican.co.za)

Find this specification on

