



System:	Pelican 60 Minute Fire Resistant Drywall for Walls up to 4.2 Metres in Height
Brand:	<b>JUMBO FireWALL 63/60/4.2m</b>
Thickness:	93mm
Wall Height:	Up to 4.2 metres
Fire Properties:	SANS 10177-2, 60min Fire Rating
Product Detail: and track	63mm Stud + 64mm Track + one 15mm Fire Resistant JUMBO Board on both sides of the Stud
Recommended Areas:	Education / Industrial / Commercial / Residential / Healthcare / Hospitality
Specification:	Pelican Systems JUMBO FireWall 63/60 with overall thickness of 93mm, with 63mm JUMBO Studs at 600mm centres friction fitted into head track and floor track and clad on both sides with a single layer of 15mm thick Fire Resistant JUMBO Board fixed at 220mm centres using 25mm Drywall Screws. All exterior joints to be covered with JUMBO Tape and finished with two layers of JUMBO Jointing Plaster applied and lightly sanded down, leaving wall surface prepared for painting, all in accordance with the supplier's recommendations.
Acoustics & Thermal Insulation:	63mm JUMBO SoundTherm will enhance performance in a fire as well as improve acoustic and thermal performance. (optional)
Accessories:	Class A (60 Minute) Fire Rated Door in a 93mm pre-galvanised frame (LH or RH) Galvanised Steel Sheets for added security
Website Resources:	BOQ Specification, Data Sheets, Revit Files and Detail Drawings

#### Typical Illustration for JUMBO® 15mm FireWALL 63/60/4.2m

