



We have teamed up with one of the major paint manufacturer's in South Africa to develop a range of JUMBO® branded products that are specifically designed to work with JUMBO® Plasterboard for both ceilings and drywalls.

Whilst we are not specialists, we have teamed up with the professionals to bring our clients three top quality products that they can use with confidence on all of the ceiling and partition work.

- JUMBO® Plaster Primer for surface preparation
- JUMBO® PVA Matt Acrylic ideal for ceilings
- JUMBO® PVA Mid-Sheen ideal for walls

**JUMBO® Plaster Primer** is a water based plaster primer which penetrates the surface and ensures optimum adhesion of top coats to the surface, while providing protection against alkali and efflorescence. It is meant for application to both uncoated new work and weathered or previously painted areas and is ideal for Plasterboard preparation for painting.

#### Features & Benefits

- Alkali resistant plaster primer
- Excellent adhesion
- Lead less than 90 ppm
- Resistant to efflorescence
- Suitable for a variety of surfaces
- Quick drying

#### Spreading Rate

This product will cover approximately 4 - 8 m<sup>2</sup> per litre per coat depending on the type of substrate, surface porosity and application method.

#### Application

Apply this product with a paint brush or Mohair roller to both smooth and rough surfaces allow at least 6 hours to dry for water based top coats and overnight to dry for solvent based top coats. This product is ready for use, thinning is not required.

**JUMBO® PVA Matt Acrylic** is water based with a quality matt finish. It has excellent hiding power with some washability for interior and exterior areas. It is meant for application to both primed and sound previously painted areas.

#### Features & Benefits

- Lead free
- Easy to apply
- Matt finish
- Rapid drying – two coats in one day
- Water clean up
- Good adhesion properties
- Interior & exterior use
- Environmentally friendly

#### Spreading Rate

Approximately 6 - 8 m<sup>2</sup> per litre per coat, depending on the type of substrate and surface porosity. Spread rates are based on the product being applied to sound smooth plaster.

#### Application

Apply this product with a paint brush or suitable paint roller, and allow two to four hours drying time between coats. This product is ready for use, thinning is not required.

**JUMBO® PVA Mid-Sheen** is an acrylic wall coating, which has been specially formulated to decorate and protect interior and exterior surfaces.

#### Features & Benefits

- Lead free
- Smooth silk finish, fully washable
- Lower odour
- Durable protective coating
- UV & weather resistant
- Easy to apply
- Water clean-up

#### Spreading Rate

This product will cover approximately 6 - 8 m<sup>2</sup> per litre per coat depending on the type of substrate, surface porosity and application method.

#### Application

Apply this product with a paint brush or suitable roller to smooth surfaces and use a quality synthetic long pile paint roller on rough / coarse surfaces. Always allow at least four hours of drying time between coats. This product is ready for use, thinning is not required.

#### Cleaning

Clean all tools (brushes & rollers) after use with water and while still wet.

*Please refer to the Technical Data Sheet and the Safety Data Sheet for further information.*

