



PVA Matt

General Description

An economical decorative high hiding paint for interior and exterior use. Can be tinted to a range of pastel shades.

Uses

Interior or exterior plastered or previously painted surfaces including ceilings but not recommended for potentially damp environments such as kitchens and bathrooms.

Physical Form	Non-flammable viscous liquid containing non-toxic pigments and extenders. Slight ammonia odour
Colour	White
Finish	Matt
Spreading Rate	Approximately 6 - 8 m ² /L per application
Polymer Type	Alkali-resistant acrylic copolymer latex
Fillers	Non-toxic extenders
Pigments	Weather and light resistant types only
Drying Properties	Surface or touch-dry: within 1 hour
Recoating Time	4 hours depending on conditions during drying
Flash Point	Not flammable in liquid form
Packaging	20L
Thinning	Not recommended, but if required to reduce viscosity add a minimum quantity of WATER. Excessive dilution degrades the quality of the product. (NB: DO NOT add solvent-based thinners such as mineral turpentine)
Cleaning	Do not allow the product to dry on equipment. Equipment is readily cleaned using water (Some detergent may be added to water to facilitate clean up)
Application Method	Supplied ready-for-use. Apply using a synthetic PVA roller (Do not use rollers designed for enamels)

Do Not Paint

- If the temperature is below 10°C or above 35°C
- If the surface is damp (moisture reading above 15%)
- If it is raining or rain is forecast
- Before 9h00 and after 16h00 in the winter

Health & Safety

Keep paint away from children and animals. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

Disclaimer Advice

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Pelican Systems cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Pelican Systems products. Paint technology is continuously being developed and Pelican Systems reserves the right to update product specifications without prior notice. Contact Pelican Systems for further details.

