



**PVA Mid-Sheen**

**General Description**

JUMBO® PVA Mid-Sheen is a luxurious acrylic wall coating, which has been specially formulated to decorate and protect interior and exterior surfaces.

**Uses**

New or previously painted cement plaster, concrete, fibre cement, gypsum plaster, brick surfaces, building boards, galvanised steel, mild steel and wood after suitable preparation and priming. Interior and exterior use.

Physical Form	Non-flammable viscous liquid containing non-toxic pigments and extenders. Slight ammonia odour
Colour	White
Finish	Mid-Sheen
Spreading Rate	Approximately 6 - 8 m <sup>2</sup> /L per application
Polymer Type	Alkali-resistant acrylic copolymer latex
Fillers	Non-toxic extenders
Pigments	Weather and light fast types only
Drying Properties	Surface or touch-dry: within 1 hour
Recoating Time	4 - 6 hours depending on conditions during drying
Flash Point	Not flammable in liquid form
Packaging	20L
Thinning	Not recommended, but if required to reduce viscosity add a minimum quantity of WATER. Excessive dilution degrades the quality of the product. (NB: DO NOT add solvent-based thinners such as mineral turpentine)
Cleaning	Do not allow the product to dry on equipment. Equipment is readily cleaned using water. (Some detergent may be added to water to facilitate clean up)
Application Method	Supplied ready-for-use. Apply using a synthetic PVA roller

**Recommended Application Procedure & Surface Preparation**

**New Surfaces:**

*Surfaces must be thoroughly clean, dry and in sound condition before painting.*

- **Cement plaster, concrete, fibre cement, brick surfaces and building boards:** Apply one coat JUMBO® Plaster Primer and two coats of JUMBO® PVA Mid-Sheen. Optional, for optimum film build and surface finish, apply Universal Undercoat prior to applying JUMBO® PVA Mid-Sheen.
- **Gypsum plaster:** Apply one coat JUMBO® Plaster Primer and two coats of JUMBO® PVA Mid-Sheen. Optional, for optimum film build and surface finish, apply Universal Undercoat prior to applying JUMBO® PVA Mid-Sheen.
- **Metal, steel and galvanised steel:** Apply one coat Metal Etch Primer or water-based Metal Primer (two coats at the coast), followed by a coat of Universal Undercoat and two coats of JUMBO® PVA Mid-Sheen.
- **Wood:** Apply one coat water or solvent based Wood Primer, then apply one coat of Universal Undercoat prior to applying two coats of JUMBO® PVA Mid-Sheen.

**Previously Painted Surfaces:**

*Thoroughly clean and prepare surface by removing all dust, dirt, grease, mould, grime and flaking paint before starting to paint.*

- **Cement plaster, concrete, fibre cement, brick surfaces and building boards:** Spot prime bare surface with one coat JUMBO® Primer and two coats of JUMBO® PVA Mid-Sheen. Optional, for optimum film build and surface finish, apply Universal Undercoat prior to applying JUMBO® PVA Mid-Sheen.
- **Gypsum plaster:** Spot prime bare surface with a coat of JUMBO® Plaster Primer and two coats of JUMBO® PVA Mid-Sheen. Optional, for optimum film build and surface finish, apply Universal Undercoat prior to applying JUMBO® PVA Mid-Sheen.
- **Metal, steel and galvanised steel:** Spot prime bare surface with one coat Metal Etch Primer or water-based Metal Primer (two coats at the coast), followed by a coat of Universal Undercoat and two coats of JUMBO® PVA Mid-Sheen.
- **Wood:** Spot prime bare surface with one coat water or solvent based Wood Primer, then apply one coat of Universal Undercoat prior to applying two coats of JUMBO® PVA Mid-Sheen.

**Do Not Paint**

- If the temperature is below 10°C or above 35°C
- If the surface is damp (moisture reading above 15%)
- If it is raining or rain is forecast
- Before 9h00 and after 16h00 in the winter

**Health & Safety**

Keep paint away from children and animals. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

**Disclaimer Advice**

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Pelican Systems cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Pelican Systems products. Paint technology is continuously being developed and Pelican Systems reserves the right to update product specifications without prior notice. Contact Pelican Systems for further details.