



Plaster Primer



General Description

JUMBO® Plaster Primer is a water-based plaster primer which penetrates the surface and ensures optimum adhesion of topcoats to the surface while providing protection against alkali and efflorescence.

Uses

New or previously painted concrete, cement plaster, fibre cement, gypsum plaster, building boards and brick surfaces after suitable preparation. Interior and exterior use.

Physical Form	Low odour, non-flammable medium viscosity liquid paint containing pigments and extenders
Colour	White
Finish	Matt
Spreading Rate	Approximately 4 - 8 m ² /L per application
Recommended DFT	35 - 45 µm per coat
Recommended WFT	110 - 114 µm per coat
Viscosity @ 23 °C	95 - 100 KU
S G@23°C	1.243 - 1.343 Kg/L
Mass Solid	45 - 50%
Volume Solid	30 - 35%
Polymer Type	New technology alkali and water-resistant acrylic copolymer latex
Fillers	Non-toxic extenders
Pigments	Non-toxic, weather and light resistant types only
Drying Properties	Surface or touch-dry: within 1 hour
Recoating Time	4 hours depending on conditions and film build
Flash Point	Not flammable in liquid form
Packaging	20L
Thinning	The product is supplied ready for use but may be thinned with a maximum of 10% by volume with clean water. Excessive dilution degrades the quality of the product
Cleaning	Do not allow the product to dry on equipment. Equipment is readily cleaned using water (Some detergent may be added to water to facilitate clean up)
Application Method	Stir the contents thoroughly with a flat paddle before use. Apply this product with a paintbrush or synthetic PVA roller, and allow 2 to 4 hours drying time between coats

Recommended Application Procedure & Surface Preparation

New Surfaces:

Surfaces must be thoroughly clean, dry and in sound condition before painting.

• **Cement plaster, concrete, fibre cement, gypsum plaster, brick surfaces and building boards:** Apply one coat JUMBO® Plaster Primer and two coats of water or solvent based topcoat. Optional, for optimum film build and surface finish, apply Universal Undercoat prior to applying topcoat.

Previously Painted Surfaces:

Thoroughly clean and prepare surface by removing all dust, dirt, grease, mould, grime and flaking paint before starting to paint.

• **Cement plaster, concrete, fibre cement, gypsum plaster, brick surfaces and building boards:** Spot prime bare surface with one coat JUMBO® Plaster Primer and two coats of water-based topcoat. Optional, for optimum film build and surface finish, apply Universal Undercoat prior to applying topcoats.

Do Not Paint

- If the temperature is below 10°C or above 35°C
- If the surface is damp (moisture reading above 15%)
- If it is raining or rain is forecast
- Before 9h00 and after 16h00 in the winter

Health & Safety

Keep paint away from children and animals. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

Disclaimer Advice

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Pelican Systems cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Pelican Systems products. Paint technology is continuously being developed and Pelican Systems reserves the right to update product specifications without prior notice. Contact Pelican Systems for further details.